

FASEPTM

MADE IN ITALY



B230-T

9M2730
OPTIONAL

B230-T B230-TC

DOTAZIONI OPTIONAL - Optinal equipment - Equipements optionnels - Extra Ausstattungen - Dotación opcional



Sistema misura applicazione guidata dei pesi adesivi. Device to measure and apply adhesive weights.



2M2762
Campana per Cono
Bell




2M2364
Cono Camion (198-225mm)
Cone (198-225mm)



9M2441
Sollevatore Mobile
Mobile lifter



9M2730
Sollevatore Pneumatico
Pneumatic Lifter



lo di protezione
tection

DOTAZIONI STANDARD - Standard equipment - Equipements standard - Standard Ausstattungen - Dotación estándar



Per Carri e Vetture
For Trucks and Cars



Per Carri
For Trucks

La Ditta si riserva di apportare modifiche alla propria produzione senza preavviso ed in qualsiasi momento. / Specifications, models and options subject to change without notice. / Fasep se réserve le droit d'apporter des changements à la conception ou au matériau pour améliorer le produit. / Änderungen unserer Produkte sind in jedem Augenblick und ohne vorherige Benachrichtigung möglich. / La empresa se reserva el derecho de aportar modificaciones a los productos en cualquier momento.

CARATTERISTICHE TECNICHE - TECHNICAL DATA - CARACTERISTIQUES TECHNIQUES - TECHNISCHE DATE - CARACTERISTICAS TECNICAS

I Alimentazione elettrica	GB Power supply	F Alimentation électrique	D Elektrischer Anschluß	E Alimentación eléctrica	220-380 50-60Hz 3Ph
Potenza assorbita	Motor rating	Puissance absorbée	Leistungsaufnahme	Potencia absorbida	200 Watt
Potenza Motore	Power Source	Poissance moteur	Motorleistung	Potencia del motor	0,35Hp
Velocità di rotazione	Balancing speed	Vitesse de rotation	Auswuchtdrehzahl	Velocidad de rotación	82RPM(50Hz) 98RPM(60Hz)
Diametro cerchio	Rim diameter	Diamètre jante	Felgendurchmesser	Diametro de llanta	8" (200 mm) - 26" (650 mm)
Larghezza ruota	Wheel Width	Largeur jante	Felgenbreite	Ancho rueda	max 20" (500 mm)
Peso ruota	Wheel Weight	Poids roue	Radgewicht	Peso rueda	max 200Kg (440 Lbs)
Tempo di equilibratura	Working time	Temps pour l'équilibrage	Zeit für die Auswuchtung	Tiempo de equilibrado	10 - 25 s.
Precisione	Accuracy	Précision	Ausflöschung	Precisión	± 2 gr. / ± 20 gr. Carri

B230-T B230-TC
DIMENSIONI Dimensions mm. 1120 L. x 550 P. x 950 H.
IMBALLO Packaging mm. 1130 L. x 760 P. x 1120 H.
PESO Weight Lordo kg 142 - Netto kg 120

FASEP 2000 s.r.l.
 Via Faentina, 96 - 50030 Ronta (Firenze) Italy - Tel. +39 055 8403126 - Fax +39 055 8403354
 e-mail: info@fasep.it www.fasep.it

